

Care@Home™ Bed Sensor



ES700BD Monitoring Sensor Pad for a Bed

Product

A monitoring sensor pad for any bed, in any home, to track a resident's movement in or out of bed, integrated with the Care@Home™ product suite

Features include:

- Two components:
 - RF sensor transceiver
 - Nonslip, waterproof, anti-microbial, pressure pad
- Warnings include:
 - Staying in bed too long
 - Leaving the bed and wandering around
 - Possibly falling, if not identified by another sensor within a predefined period
- Dual LED (green/red) for detection status indication
- Modern, stylish, compact design
- Easy to clean and maintain

Smart Care

Essence Care@Home™ multi service platform is an Aging-in-Place product suite that offers a seamless health monitoring experience allowing independence for seniors and peace of mind to their loved ones.

Care@Home™ allows service providers the flexibility to offer their customers services ranging from emergency alerting to a professional intelligent home care solution, which constantly learns and adapts to the daily behavior of individuals and provides alerts with different severity levels based on deviation from the daily routine.

The Care@Home multi service platform includes:

- Care@Home PERS + Advanced Emergency Response Alarm
- Care@Home Family Monitoring
- Care@Home Pro Intelligent Home Care Solution

Specifications

COMMUNICATIONS

- Maximum RF range: Up to 400 m (1,312 ft.) open air
- Protocols: Proprietary bi-directional radio protocol
- Modulation and frequency: FSK modulation:
 - 868.3 MHz (China)
 - 869.225 MHz (Europe)
 - 916.5 MHz (North America and Australia)
 - 916.3 MHz (Israel)
- Data security: 32-bit ID, over 4 billion combinations

TRANSCEIVER SECURITY

- Tamper mechanism for open cover
- Visual indications: 1 green and 1 red LED

SENSITIVITY

Nominal detection threshold: 22 kg (50 lbs.)

POWER CONSUMPTION

- Batteries: 3V CR123A lithium battery
- Battery life: Up to 3 years

DIMENSIONS

- Size (H x W x D):
 - Transceiver: 98 x 25 x 25 mm 3.86 x 0.98 x 0.98 in.
 - Pressure pad: 76.2 x 27.94 x 0.8 cm 30 x 11 x 0.3 in.

ENVIRONMENT

- Storage ambient temperature range: -20°C 70°C (-4°F 158°F)
- Operating ambient temperature range: 0°C 49°C (32°F 120°F)
- Operating humidity: Up to 93% non-condensing

COMPLIANCE

• CE, FCC, IC, UL









